



Low VOC LATICRETE® Products / LEED Certification (LEED v4) TDS 251

LATICRETE International, Inc. produces an assortment of portland cement and epoxy based setting and grouting materials. The LEED Projects program is gaining more popularity with architectural firms and building design groups. The following LATICRETE® product information is to be used for building projects that need to comply with LEED v4 certification.

LATICRETE International, Inc., the world leader in tile and stone installation materials, has become the first tile and stone installation material manufacturer to receive UL GREENGUARD Gold certification for their products. For specific information regarding which products and systems are UL GREENGUARD Gold certified please visit our web site at www.laticrete.com/green.

For all of your job specific LEED certifications of LATICRETE products, please visit www.laticrete.com to access the LATICRETE LEED Project Certification Assistant.

LATICRETE International, Inc. packaging and most of the products, do not contain any post-consumer or pre-consumer recycled content. LATICRETE plastic bags and buckets are recyclable and may help contribute to LEED Materials and Resources Credit - Construction and Demolition Waste Management.

125 Sound & Crack Isolation Adhesive contains 35% post-consumer recycled content, and 170 Sound & Crack Isolation Mat contains 89.5% post-consumer recycled content. Several LATICRETE thin-set mortars and self-leveling underlayments also contain pre-consumer recycled content. These products will contribute to LEED Materials and Resources Credit – Building Product Disclosure and Optimization-Sourcing of Raw Materials.

LATICRETE products may help contribute to the following LEED v4 Credits (unless otherwise noted);

- Materials and Resources Credit – Building Product Disclosure and Optimization-Environmental Product Declarations
- Materials and Resources Credit – Building Product Disclosure and Optimization-Sourcing of Raw Materials
- Materials and Resources Credit – Building Product Disclosure and Optimization –Material Ingredients
- Materials and Resources Credit – Construction and Demolition Waste Management
- Materials and Resources Credit – Building Life-Cycle Impact Reduction
- Indoor Environmental Quality Credit – Construction Indoor Air Quality Management Plan
- Indoor Environmental Quality Credit – Low-Emitting Materials
- Indoor Environmental Quality Credit – Indoor Air Quality Assessment (Option 2 Air Testing)

Most LATICRETE portland cement and sand based products are manufactured at our local facilities. Many of the raw materials used to manufacture these products supplied are sourced from within a 100 mile (162 km) radius. The LATICRETE International Inc. facility locations are as follows:

LATICRETE International, Inc. 1 LATICRETE Park North Bethany, CT 06524	LATICRETE International, Inc. 22740 Temescal Canyon Road Corona, CA 92883	LATICRETE International, Inc. 1710 111th Street Grand Prairie, TX 75050
LATICRETE International, Inc. 6769 White Drive West Palm Beach, FL 33407	LATICRETE International, Inc. 4620 West 84 th St. Building II, Suite 200 Indianapolis, IN 46268	LATICRETE International, Inc. 1 Laticrete Park South East 299 Industry Dr. Hamlet, NC 28345
LATICRETE International, Inc. 1 Laticrete Park Pacific North West 100 Entek Way Lebanon, OR 97355	LATICRETE International (L&M) 412 Laurel St. Pottstown, PA 19464	

PORTLAND CEMENT BASED ADHESIVES, UNDERLAYMENTS AND GROUTS:

The following product materials are of a washed sand (to minimize silica dust) or limestone (unsanded) and portland cement product with no VOC content. Since the product is a sand and portland cement blend the hardened, cured product can be disposed of as a crushed, recyclable aggregate.

Product Name	VOC Content
1500 Sanded Grout † ♡	0.00 g/L ^
1600 Unsanded Grout † ♡	0.00 g/L ^
PERMACOLOR® Grout † ♡	0.00 g/L ^
PERMACOLOR Select † ♡ United States Invention Patent No: 6,784,229 (and other Patents)	0.00 g/L ^
PERMACOLOR Select NS ♡	0.00 g/L ^
MVIS™ Pointing Mortar ♡	0.00 g/L ^
MVIS Premium Pointing Mortar ♡	0.00 g/L ^
226 Thick Bed Mortar †	0.00 g/L ^
3701 Fortified Mortar †	0.00 g/L ^
MVIS Premium Mortar Bed †	0.00 g/L ^
211 Powder † *	0.00 g/L ^
255 MULTIMAX™ † * United States Invention Patent No.: 6,784,229 (and other Patents)	0.00 g/L ^
MULTIMAX™ LITE † *	0.00 g/L ^
254 Platinum † *	0.00 g/L ^
254R Platinum Rapid *	0.00 g/L ^
257 Titanium † *	0.00 g/L ^
125 Sound & Crack Adhesive † *	0.00 g/L ^
SURE SET™ † *	0.00 g/L ^
253 Gold † *	0.00 g/L ^
253R Gold Rapid *	0.00 g/L ^
252 Silver † *	0.00 g/L ^
LHT *	0.00 g/L ^
LHT PLUS™ *	0.00 g/L ^
Glass Tile Adhesive † *	0.00 g/L ^
4-XLT † *	0.00 g/L ^
4-XLT Rapid *	2.56 g/L ^
TRI-LITE™ † *	0.00 g/L ^
272 Mortar † *	0.00 g/L ^
317 Mortar † *	0.00 g/L ^
MVIS Veneer Mortar † *	0.00 g/L ^
MVIS Hi-Bond Veneer Mortar † *	0.00 g/L ^
MVIS Hi-Bond Rapid Veneer Mortar *	0.00 g/L ^
MVIS LIGHTWEIGHT Mortar *	0.00 g/L ^
MVIS Thin Brick Mortar *	0.00 g/L ^
220 Marble & Granite Mortar † *	0.00 g/L ^
209 Floor Mud	0.00 g/L ^
NXT™ Level Plus † ♦	0.00 g/L ^
NXT Level ♦	0.00 g/L ^
NXT Patch	0.00 g/L ^
NXT Skim	0.00 g/L ^
NXT Level DL † ♦	0.00 g/L ^
DRYTEK LEVELEX Plus † ♦	0.00 g/L ^
DRYTEK® LEVELEX™ † ♦	0.00 g/L ^
DRYTEK Patch	0.00 g/L ^
DRYTEK Skimcoat	0.00 g/L ^
LATICRETE® SUPERCAP® SC500 (Concentrate) † ♦	0.00 g/L ^
LATICRETE SUPERCAP SC500 (Sanded) † ♦	0.00 g/L ^
LATICRETE SUPERCAP SC500 Plus	0.00 g/L ^
LATICRETE SUPERCAP SC500 LW	0.00 g/L ^
LATICRETE SUPERCAP Skimcoat	0.00 g/L ^

ADDITIVES / PRIMERS:

The following additives have negligible VOC content.

NOTE: The following products are manufactured at our Bethany, CT location with some possibly manufactured in our Grand Prairie, TX facility. LATICRETE PRIME N' BOND is manufactured in North East OH.

Product Name	VOC Content
3701 Mortar Admix †	<2.39 g/L ^
4237 Latex Additive †	<2.39 g/L ^
333 Flexible Additive	<2.39 g/L ^
8510 Bonding Admix	<2.39 g/L ^
101 Rapid Latex Admix	<2.39 g/L ^
1776 Grout Enhancer †	<2.39 g/L ^
73 Crete Admix	<2.39 g/L ^
3642 Latex Concentrate	<2.39 g/L ^
PRIME N' BOND	0.9 g/L °
NXT™ Primer †	7.00 g/L ^
DRYTEK® LEVELEX™ Primer †	7.00 g/L °
LATICRETE® SUPERCAP® Primer Plus †	7.00 g/L °
Fracture Ban™ Primer	7.00 g/L °
STRATA_HEAT™ Thermal Pack	0.00 g/L ^

MEMBRANES:

The following membrane products have negligible VOC content.

NOTE: The following products are manufactured at our Bethany, CT location (except for STRATA_MAT™ and STRATA_MAT XT).

Product Name	VOC Content
Blue 92 Anti-Fracture Membrane †	2.39 g/L *
HYDRO BAN® †	2.39 g/L *
MVIST™ Air & Water Barrier †	2.39 g/L *
9235 Waterproofing Membrane † (Tested per EPA Method 24)	2.39 g/L *
STRATA_MAT™ †	N/A
STRATA_MAT XT	N/A
HYDRO BAN Sheet Membrane	N/A
HYDRO BARRIER™	2.39 g/L *
9237 Waterproofing Membrane	2.39 g/L *
LATAPOXY® Waterproof Flashing Mortar	3.36 g/L *

EPOXY PRODUCTS:

The following epoxy products have negligible VOC content.

NOTE: The following products are manufactured at our Bethany, CT location.

Product Name	VOC Content
LATAPOXY 300 Adhesive †	0.80 g/L ^
LATAPOXY BIOGREEN™ 300 Adhesive	18.00 g/L ^
LATAPOXY 210 Modified Epoxy Adhesive	0.00 g/L ^
LATAPOXY 310 Stone Adhesive	<0.65 g/L ^
LATAPOXY 310 Rapid Stone Adhesive	<1.01 g/L ^
LATICRETE NXT Vapor Reduction Coating †	9.4 g/L □
SPARTACOTE Moisture Vapor Barrier †	9.4 g/L □
LATICRETE SUPERCAP Moisture Vapor Control †	9.4 g/L □
NXT™ Epoxy Primer	36.00 g/L °
LATAPOXY SP-100	0.80 g/L ^
SPECTRALOCK® DAZZLE™	0.00 g/L ^
SPECTRALOCK 2000 IG †	0.80 g/L ^
SPECTRALOCK PRO Premium Grout †	0.031 g/L ^
United States Invention Patent No.: 6,881,768 (and other Patents)	

SPECTRALOCK PRO Grout [†] United States Invention Patent No.: 6,881,768 (and other Patents)	0.031 g/L ^
MVIS Epoxy Pointing Mortar	0.031 g/L ^

MASTIC:

The following products are organic based adhesives.

Product Name	VOC Content
15 Premium Mastic	35.95 g/L ^

SEALANT:

The following products are sealants and a primer.

Product Name	VOC Content
Premium Acrylic Caulk	50 g/L #
LATASIL™	37.16 g/L #
LATASIL 9118 Primer	748.17 g/L ~

SOUND CONTROL:

NOTE: The following product is manufactured at our Bethany, CT and Grand Prairie, TX locations only.

Product Name	VOC Content
125 Sound & Crack Adhesive [†]	0.00 g/L ^

SPARTACOTE:

Product Name	VOC Content
SPARTACOTE FLEX SB™ (Clear)	330 g/L
SPARTACOTE FLEX XT™	90 g/L ^o
SPARTACOTE FLEX PURE™	61 g/L ^o
SPARTACOTE FLEX PURE CLINICAL PLUS™	61 g/L ^o
SPARTACOTE FLEX SB Low Gloss	340 g/L
SPARTACOTE FLEX SB with any SPARTACOTE Polyaspartic Pigment	266 g/L
SPARTACOTE FLEX XPL	30.1 g/L ^o
SPARTACOTE SurfaceBuild 110™	40 g/L ^o
SPARTACOTE SurfaceBuild 150™	9.29 g/L ^o
SPARTACOTE Epoxy Membrane	20 g/L ^o
SPARTACOTE Surface Build Top Coat UV	15 g/L ^o
SPARTACOTE Vertical HB	10 g/L ^o
SPARTACOTE Epoxy Fill Coat	35 g/L ^o
SPARTACOTE SL Topping	15 g/L ^o
SPARTACOTE Urethane Primer WB	5 g/L ^o
SPARTACOTE Cove Gel	30 g/L ^o
SPARTACOTE General Primer	15 g/L ^o
SPARTACOTE Oil Tolerant Primer	15 g/L ^o
SPARTACOTE Vertical WB	5 g/L ^o
SPARTACOTE Surface Build Quartz	6 g/L ^o
SPARTACOTE Surface Build Flake	15 g/L ^o
SPARTACOTE Urethane Floor Sealer	5 g/L ^o

SEALERS (LOW-SOLIDS COATING):

NOTE: The following Low Solids Coating products are manufactured in West Central CA. Cleaners are not subject to VOC requirements in LEED v4.

Product Name	(Low-Solids) VOC Content including water
STONETECH® Bulletproof® Sealer	12 g/L**
STONETECH Enhancer Sealer	19 g/L**
STONETECH Grout Release	7 g/L**
STONETECH Heavy Duty Grout Sealer	3 g/L**

STONETECH Heavy Duty Exterior Sealer (solvent based)	724 g/L
STONETECH Heavy Duty Sealer	8 g/L**
STONETECH Impregnator Pro [®] Sealer (solvent based)	748 g/L
STONETECH Natural Stone Countertop Sealer	8 g/L**
STONETECH Salt Water Resistant Sealer	66 g/L**
STONETECH Sealer	2 g/L**
Stone Care Premium Stone Sealer	2 g/L**
Stone Care Granite and Marble Countertop Sealer	2 g/L**
Stone Care Stone Sealer	2 g/L**
Stone Care Salt Water Resistant Sealer	66 g/L**
Stone Care Enhancer & Sealer	19 g/L**
Stone Care Granite and Marble Countertop Polish	23 g/L**

SEALERS

NOTE: The following Low Solids Coating products are manufactured in West Central CA. Cleaners are not subject to VOC requirements in LEED v4.

Product Name	VOC Content
STONETECH High Gloss Finishing Sealer	80 g/L [∞]
STONETECH Semi Gloss Finishing Sealer	52 g/L [∞]
STONETECH Enhancer Pro (solvent based)	632 g/L
STONETECH Polish (not a coating or sealer)	23 g/L
Stone Care High Gloss Sealer & Finish	80 g/L [∞]
Stone Care Semi Gloss Sealer & Finish	52 g/L [∞]

L&M Construction Chemicals:

Low Solids Coatings (Sealers):

NOTE: Low Solids Coatings product calculations include water.

Product Name	(Low Solids) VOC Content including water
L&M AQUAPEL [™]	7 g/L**
L&M AQUAPEL PLUS [™]	10 g/L**
L&M PETROTEX [™]	7 g/L**

Sealers:

Product Name	VOC Content
L&M LUMISEAL FX [™]	116 g/L [~]
L&M LUMISEAL PLUS [™]	697 g/L
L&M LUMISEAL WB [™]	99 g/L ^Δ
L&M LUMISEAL WB PLUS [™]	40 g/L

Concrete Curing Compounds:

Product Name	VOC Content
L&M CHEM HARD [™]	0.00 g/L ^Δ
L&M E-CON [™]	63 g/L ^Δ
L&M FGS HARDENER PLUS [™]	0.00 g/L ^Δ
L&M CURE [™]	0.00 g/L ^Δ
L&M CURE R [™]	305 g/L
L&M CURE R RED DYE [™]	305 g/L
L&M CURE R2 [™]	325 g/L
L&M CURE W	1.1 g/L ^Δ
L&M CURE W2	0.9 g/L ^Δ
L&M LION HARD [®]	6.1 g/L ^Δ
L&M SEAL HARD [®]	0.00 g/L ^Δ

Concrete Curing & Sealing Compounds:

Product Name	VOC Content
L&M DRESS & SEAL™	690 g/L
L&M DRESS & SEAL 30™	688 g/L
L&M DRESS & SEAL WB 30™	184 g/L

Form Release Compounds:

Product Name	VOC Content
L&M DEBOND®	4.2 g/L ^Δ
L&M DEBOND GOLD™	4.2 g/L ^Δ
L&M EZ STRIP™	4.5 g/L ^Δ

Emery Topping and Dry-Shake Hardeners:

The following L&M products are manufactured in Bayville, NJ.

Product Name	VOC Content
L&M EMERYTOP 400™	0.0 g/L
L&M EMERYPLATE FF™	0.0 g/L
L&M QUARTZPLATE FF™	0.0 g/L
L&M TRAP ROCK™	0.0 g/L

Structural Grouts and Patches:

The following L&M products are manufactured in Grand Prairie, TX.

Product Name	VOC Content
L&M CRYSTEX®	0.0 g/L
L&M DURACRETE™	0.0 g/L
L&M DURAGROUT™	0.0 g/L
L&M DURAPATCH HIWAY™	0.0 g/L
L&M DURAPATCH INDUSTRIAL™	0.0 g/L
L&M DURAPATCH VOH™	0.0 g/L
L&M DURAPLUG™	0.0 g/L
L&M FASTRAK™	0.0 g/L

L&M Cleaner:

The following L&M products is manufactured in Pottstown, PA.

Product Name	VOC Content
L&M CITREX®	111.2 g/L

L&M Latex Additive / Primer:

The following L&M products is manufactured in Pottstown, PA.

Product Name	VOC Content
L&M EVERBOND™	25 g/L [^]

- † UL GREENGUARD Gold certified products. Please visit www.laticrete.com/green for UL GREENGUARD Gold certificates.
 - ^ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1168 (65 g/L less water) **and** Bay Area Air Quality Management District (BAAQMD) Regulation 8, Rule 51 (130 g/L).
 - # Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1168 (250 g/L less water) **and** Bay Area Air Quality Management District (BAAQMD) Regulation 8, Rule 51 (250 g/L).
 - * Meets the VOC requirements of South Coast Air Quality Management District Rule #1113 (100 g/L less water) and LEED 2009 (v3) Credit 4.2.
 - ** Meets the VOC requirements of South Coast Air Quality Management District Rule #1113 (120 g/L including water) and LEED 2009 (v3) Credit 4.2 and LEED v4 Credit Low Emitting Materials as a Low-Solids Coating.
 - ~ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1168 for Architectural porous sealant primers (775 g/L less water).
 - ⊖ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Industrial Maintenance Coatings (100 g/L less water).
 - ° Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Primers, Sealers, Undercoaters (100 g/L less water).
 - △ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Concrete Curing Compounds (100 g/L less water).
 - ◊ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Form Release Compounds (100 g/L less water).
 - ∞ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Tile and Stone Sealers (100 g/L less water).
 - ∨ Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Waterproofing Sealers (100 g/L less water).
 - Meets the VOC requirements of South Coast Air Quality Management District (SCAQMD) Rule #1113 for Floor Coatings (50 g/L less water).
 - ♥ Product Specific (Type III) Environmental Product Declaration - Cement Grout for Tile Installation.
 - ♣ Product Specific (Type III) Environmental Product Declaration - Cement Mortar for Tile Installation.
 - ♦ Product Specific (Type III) Environmental Product Declaration – Cement Self-Leveling Underlayment.
- N/A Not Applicable

Technical Data Sheets are subject to change without notice. For latest revision, check our website at www.laticrete.com
 TDS 251.doc R 9 January 2019



LATICRETE INTERNATIONAL, INC. ▪ 1 LATICRETE Park North ▪ Bethany, CT 06524-3423 USA
 800.243.4788 ▪ support@laticrete.com ▪ www.laticrete.com

©2014 LATICRETE INTERNATIONAL, INC. All trademarks shown are the intellectual properties of their respective owners.